


Treffler Milling Machinery QUALITY STARTS WITH MILLING!

Flockomat Absolutely dust-free.	
Absolutely dust-free	
Infinitely adjustable	
Thick- and thin-rolled flakes	
Accurate-to-the-gram product	tion

Treffler Flakomat. Singling out grain. Freshly flaked.

High-quality flakes for healthy muesli or as decoration. Flaked (pseudo) grains have many uses: for bakers, millers or farm marketers, the dust-free flaking plant is the answer to maintaining the excellent quality of the food.

DESIGN OF THE FLAKOMAT What makes the Flakomat so special?



FLAKOMAT TECHNICAL DATA

1 Mode of operation

Two profiled rollers are driven at a ratio of 1:1 to ensure evenly flaked material. The gap between the rollers can be adjusted as required from 0.01 mm to 5 mm.

2 Feed-in

The food-safe hopper is equipped with a magnetic separator. The material to be ground is continuously fed in by the electric volume-dosing system.

3 Extraction

A vacuum regulator can be used to determine how much fine flour the flakes should contain.

4 Fully automatic control

Full and empty indicators shut the machine down as required, so that continuous monitoring of the machine is not necessary.

5 Installation options

The Flakomat can be integrated into fully automatic systems. It can also be installed on a floor plate together with the Shrotomat and a dust extraction system.

Technical data FLAKOMAT 100

Output: Weight: Roller width: 5.0 kW approx. 350 kg 100 mm Required connection voltage: 400 V 16 A Dimensions (LxWxH): 1.2 x 0.8 x 1.67 m

FEED MATERIAL

In addition to common varieties of grain, pseudo grains can also be processed.





TREFFLER Maschinenbau GmbH & Co. KG

Reichersteiner Straße 24 | 86554 Pöttmes-Echsheim | Germany Phone: +49 (0) 82 53 / 99 58-0 | Fax: +49 (0) 82 53 / 99 58-70 info@treffler.net | www.treffler.net

